

LS8 2150A/2 LS082150A2FVA000

QUALITY MANAGEMENT SYSTEM
CERTIFIED BY DNV

150 9001:2000

Dual 8-Way Active Splitter (950-2150 MHz)

General Description:

The **LS082150A2FVA000** is a dual 8-way active splitter that meets strict level and match specifications achieved through the use of Quintech's proprietary microstrip and SMT technology. It operates over the 950-2150 MHz frequency range and permits signal splitting with zero loss, eliminating the need for external distribution amplifiers. The LS082150A2FVA000 provides LNB DC power insertion that can be switched on or off via the front panel mounted slide switch(es) (see LNB Power specification below).

Note: All unused RF output ports must have 75 Ω terminations.

Specifications:

Noise Figure:

Certifications:

Frequency: 950-2150 MHz

Impedance: 75 Ω P1dB: 0 dBm OIP3: 10 dBm 0 + 2 dBInsertion Loss: **Frequency Response:** + 1 dB Isolation: 18 dB **Input Return Loss:** 13 dB **Output Return Loss:** 16 dB

RF Connectors: Type F, 75 Ω

Power Requirements: 18-24 V==-, @1A via 2-pin quick connect barrier strip

CE

7 dB

LNB Power: 18 V --- (800 mA max. available for LNB power)

Power Consumption: 12 W (plus customer LNB power load)

Mechanical: 1 RU (1.75" H x 19" W x 6.5" D)

Weight: 5.6 lbs. gross (boxed), 3.0 lbs. net

0.0 lb0. grobb (b0xcd),



Provided by: Mega Hertz 800-883-8839 sales@go2mhz.com www.go2mhz.com