



Model #: SU3000RTXL3U

SmartOnline Expandable 3U Rack / Tower UPS System - On-line, double-conversion, sine wave UPS with PDU switching, current monitoring and fault tolerant auto-bypass

Highlights

- 3000VA / 2400W on-line, double-conversion, extended-run 3U rack / tower UPS
- Zero transfer time, on-line, double-conversion and economy-mode operation supported
- Maintains sine-wave 110/120V +/-2% output during overvoltages to 150 and brownouts as low as 65V (50/60Hz auto-sensing)
- Simultaneous use communications via HID compliant USB port, serial port, SNMP/Web card slot and EPO interface
- Fault tolerant auto-bypass mode, current monitoring and switched PDU control via 2 switchable output load banks
- Input: NEMA L5-30P (120V) / Output: 4 NEMA5-15R, 4 NEMA5-15/20R & 1 NEMA L5-30R (120V)
- 2 year product warranty / \$250,000 [Ultimate Lifetime Insurance](#) (USA & Canada only)



Description

3000VA on-line, double-conversion UPS system for critical server, network and telecommunications equipment. 3U rackmount form factor with an installed depth of 26 inches. Expandable battery runtime with optional BP72V15-2U (limit 1) and BP72V28RT-3U (multi-pack compatible) external battery packs. Full time sine wave 110 or 120V output with +/-2% voltage regulation. Online, double-conversion Uninterruptible Power Supply (UPS) actively converts raw incoming AC power to DC, then re-converts output back to completely regulated, filtered AC output. Operates continuously without using battery power during brownouts to 65V and overvoltages to 150V. Highly efficient operation in optional economy mode saves BTU heat output and energy costs. NEMA L5-30P input plug. NEMA 5-15, NEMA 5-15/20R and NEMA L5-30R output receptacles. Network-grade AC surge and noise suppression. Zero transfer time between AC and battery operation. Network management interfaces support simultaneous communications via USB port, DB9 serial port and SNMPWEBCARD slot. Built-in DB9 port offers both enhanced RS-232 enabled monitoring data, plus contact closure monitoring ability. HID-compliant USB interface enables integration with built-in power management and auto shutdown features of Windows and Mac OS X. Supports simultaneous detailed monitoring of equipment load levels, self-test data and utility power conditions via all 3 network interfaces. Includes PowerAlert monitoring software and complete cabling. Emergency Power Off (EPO) interface. Integrated two-bank PDU switching supports load shedding and remote reboot of connected equipment. 3-stage metered current monitoring and battery charge status LEDs. LED display panel easily rotates for viewing in rackmount or tower configurations. Dataline surge suppression for dialup, DSL or network Ethernet connection. Utility power and voltage regulation LEDs. Audible alarm. Self-test. Fault-tolerant auto-bypass mode. 4-post rackmount accessories included; 2-9USTAND tower kit and 2POSTRMKITWM 2-post rackmount accessories available. Field-replaceable, hot-swappable internal batteries and external battery packs. Attractive all-black color scheme. 2-year warranty and \$250,000 [connected equipment insurance](#); extended warranty and service contracts available.

Package Includes

- SU3000RTXL3U UPS System
- PowerAlert Software and Cabling

- Mounting hardware for 4 post rack enclosures
- Instruction manual

Features

- SmartOnline high performance UPS system is ideal for critical voice, data, medical and industrial network applications
 - True on-line, double-conversion UPS provides perfectly regulated sine wave output within 2% of 110/120V (user selectable) under all usage conditions
 - Maintains continuous operation through blackouts, voltage fluctuations and surges with zero transfer time
 - Highly efficient operation in optional economy mode setting, saving BTU heat output and energy costs
 - Removes harmonic distortion, fast electrical impulses, frequency variations and other hard to solve power problems not addressed by other UPS types
 - Corrects line voltage conditions as low as 65V and as high as 150V back to selectable 110/120V (+/-2%) values
 - Standard internal battery set offers 14 minutes runtime at half load (1200W) and 5 minutes at full load (2400W)
 - Expandable battery runtime with optional BP72V15-2U (limit 1) and BP72V28RT-3U (no limit) external battery packs
 - Compact rackmount form factor installs using only 3 rack spaces (3U) with a maximum installed depth of 26 inches
 - Ships with all mounting accessories for 4 post rackmount installation
 - Optional 2POSTRMKITWM enables 2 post rackmount installation (not wallmount compatible)
- Optional 2-9USTAND accessory enables small-footprint upright tower placement
 - Fault tolerant auto-bypass maintains continuous utility output to connected equipment, even in cases where the UPS suffers internal failure and requires maintenance
 - Network interfaces support simultaneous communications via built-in USB, DB9 serial / contact-closure and SNMPWEBCARD slot
 - HID compliant USB interface enables integration with built-in power management and auto shutdown features of Windows and Mac OS X
- Included PowerAlert UPS monitoring software supports safe unattended shutdown, monitoring and control via local connected servers, plus any number of additional servers over IP
 - UPS interface supports on-battery, low-battery, power-restored, AC-voltage, DC-voltage, output current monitoring, battery charge current, battery capacity, AC line frequency, timed inverter shutoff, activate self-test, load bank output power control and remote reboot, UPS nominal voltage adjustment and UPS line to battery power voltage setpoints
 - Built-in Emergency Power Off (EPO) interface with cable
 - NEMA L5-30P input plug; NEMA 5-15/20R & L5-30R output receptacles
 - Integrated 2 bank switched PDU enables remote outlet management for load shedding or remote reboot of individual load banks (each bank has four outlets)
 - Front panel LEDs offer current monitoring and battery charge level information
 - UPS ships fully assembled in full compliance with DOT regulations; no time consuming connection of internal batteries by user required
 - Single line TEL/DSL or network ethernet line surge suppression
 - 2 year manufacturer's product warranty, \$250,000 [Ultimate Lifetime Insurance](#)

Specifications

OUTPUT	
Output Volt Amp Capacity (VA)	3000
Output kVA capacity (kVA)	3
Output Watt Capacity (watts)	2400
Output kW capacity	2.4
Output power factor	0.8
Crest Factor	3:1
Nominal Output Voltage(s) Supported	110V; 120V
Nominal Voltage details	120V default

Frequency compatibility	50 / 60 Hz
Frequency compatibility details	Output frequency matches input nominal on startup, defaults to 60 Hz on cold-start
Output voltage regulation (line mode)	+/- 2%
Output voltage regulation (Economy line mode)	+/- 10%
Output voltage regulation (Battery mode)	+/- 2%
Built-in UPS output receptacles	4 5-15R outlet(s); 4 5-15/20R outlet(s); 1 L5-30R outlet(s)
Built-in controllable switched load banks	Two switchable four-outlet load banks, (bank 1 - four 5-15/20R, bank 2 - four 5-15R outlets)
Output circuit breaker	15A branch rated (x2) - each breaker protects 4 outlets, L5-30R is unbreakered
Basic PDU options	PDU2430 (1U / 24 5-15R outlets)
Metered PDU options	PDUMV30 (0U / 24 5-15/20R outlets)
Switched PDU options	PDUMH30NET (2U / 16 5-15/20R outlets); PDUMV30NET (0U / 24 5-15/20R outlets)
External PDU redundancy options	*ATS switch options PDUMH20AT & PDUMH20ATNET support dual UPS and hot-swappable UPS configurations
Output AC waveform (AC mode)	Sine wave
Output AC waveform (battery mode)	Sine wave
INPUT	
Rated input current (at maximum load)	24A
Nominal Input Voltage(s) Supported	110V AC; 120V AC
UPS input connection type	L5-30P
Input circuit breaker	40A
UPS Input cord length (ft.)	10
UPS Input cord length (m)	3
Recommended Electrical Service	30A 120V
BATTERY	
Full load runtime (minutes)	5 min. (2400w)
Half load runtime (minutes)	14 min. (1200w)

Expandable battery runtime	Supports extended runtime with optional external battery packs
External battery pack compatibility	BP72V15-2U (limit 1); BP72V28RT-3U (multi-pack compatible)
DC system voltage (VDC)	72
Battery recharge rate (included batteries)	Less than 6 hours from 10% to 80%
Replacement battery cartridge (internal UPS battery replacement)	RBC96-3U (quantity 1)
Battery Access	Front panel battery access door
Battery replacement description	Hot-swappable, user replaceable batteries
VOLTAGE REGULATION	
Voltage regulation description	Online, double-conversion power conditioning
Overvoltage correction	2% output voltage regulation during overvoltages to 150
Undervoltage correction	2% output voltage regulation during undervoltages to 80
Severe undervoltage correction	2% output voltage regulation during undervoltages to 65 (under 70% load only)
LEDS ALARMS & SWITCHES	
LED Indicators	14 LEDs indicate line power, online mode, economy/bypass mode, on-battery, overload, battery low, replace battery and fault status information; 4-LED meter displays load and battery charge levels; LED panel rotates for viewing in rack/tower formats
Alarms	Audible alarm indicates UPS startup, power-failure, low-battery, overload, UPS fault and remote shutdown conditions
Alarm cancel operation	Power-fail alarm can be silenced using alarm-cancel switch
Switches	2 switches control off/on power status and alarm-cancel/self-test operation
SURGE / NOISE SUPPRESSION	
UPS AC suppression joule rating	510
UPS AC suppression response time	Instantaneous
UPS Dataline suppression	1 line TEL / DSL or 10Base T Ethernet protection
EMI / RFI AC noise suppression	Yes
PHYSICAL	
Installation form factors supported with included accessories	4 post 19 inch rackmount (mounting rail kit included)

Installation form factors supported with optional accessories	2 post rackmount (2POSTRMKITWM); Tower (2-9USTAND)
Optional mounting accessory notes	Wallmount installation not recommended
Primary form factor	Rackmount
UPS / Power Module dimensions in primary form factor (height x width x depth / inches)	5.2 x 17.8 x 26
UPS / Power Module dimensions in primary form factor (height x width x depth / cm)	13.3 x 45.1 x 66
Installed whole system total rack space height (rack spaces)	3U
Secondary form factor	Tower (requires 2-9USTAND)
Installed whole system dimensions in secondary form factor (height x width x depth / inches)	17.8 x 5.2 x 26
UPS dimensions in secondary form factor (height x width x depth / cm)	45.1 x 13.3 x 66
UPS / Power Module weight (lbs)	73.8
UPS / Power Module weight (kg)	33.5
UPS Shipping dimensions (height x width x depth / inches)	11.2 x 23 x 31.5
UPS Shipping dimensions (height x width x depth / cm)	28.6 x 58.4 x 80
Shipping weight (lbs)	112.4
Shipping weight (kg)	51
UPS housing material	Steel
Cooling method	Fan
ENVIRONMENTAL	
Operating Temperature Range	+32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius
Storage Temperature Range	+5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius
Relative Humidity	0 to 95%, non-condensing

