



More broadcasting & expandability with less hardware!

The HyperCaster AIO+ (All-In-One Plus) B2000 gives you ultimate playback flexibility in a powerful, multi-channel broadcast server with more IO expansion. One to twenty channels of Playback & Recording, native SDI, NDI & IP Switching, and Graphics all-in-one! Streaming and Transport Stream output options, including SDI/IP Simulcast. Perfect for stations broadcasting to multiple destinations, including Cable, Streaming, OTT, and Social Media. Integrated Community Bulletin Board Option. Includes a user-friendly, access-from-anywhere, browser-based interface for scheduling, content management, monitoring, and designing on-air graphics. Powerful, rules-based automation saves you valuable time. Simplify your workflow, trim your equipment, and get the best of both SDI & IP with the HyperCaster AIO+.

INPUTS

- Up to 12 auto-sensing HD-SDI inputs
- Play, Record, and Switch SDI & NDI
- StreamThru™ IP Switching
- Optional IP Capture
- Import Virtually Any File Format
- Streams: RTMP Push/Pull, HLS, DASH, RTSP, SRT, TS, Zoom, Social Media
- Resumable Browser-based Uploads

OUTPUTS

- Downstream Graphics On All Sources
- Logos, Tickers, Snipes, Squeezebacks
- Remote Confidence Monitoring/Preview
- Built-in Up & Down Conversion
- CEA-608/708 Closed Captions
- Optional SDI & IP Simulcast
- Optional ABR Streaming or IP Output
- Optional Real-time CALM Audio Control

AND BECAUSE IT'S A TELVUE SERVER, YOU ALSO GET:

- Secure, Easy, Browser-based Content, Scheduling, and Remote Management Tools
- Time-saving Automatic Scheduling, Graphics, Streaming, and Workflow Rules
- 24/7 Support – Expandable Design – Future-Proof Technology – Reliable Linux OS
- Powerful Options
 - Streaming, Mobile Apps & OTT Integration with TelVue CloudCast™
 - Cloud Contributor Upload & Media Exchange with TelVue Connect™
 - TelVue InfoVue™ Broadcast Digital Signage & Community Bulletin Board Integration
 - TelVue SmartCaption™ Automatic Live & File Closed Captioning
 - Archive Integration (NAS, Archive.org)

HyperCaster® AIO+ B2000 Specifications

Models	B2000-4+	B2000-8+	B2000-12+	B2000-12X+
Max Playback	2	3	8	12
I/O Mix Playback+Encodes	2 Standard, Expandable to 5	3 Standard, Expandable to 5	5 Standard, Expandable to 8	8 Standard, Expandable to 20
Configurable HD-SDI Ports	4	8	12	12
Media Storage	5.5TB, 4x RAID5, Up to 64TB, 8x RAID6	11TB, 8x RAID6, Up to 64TB	11TB, 8x RAID6, Up to 64TB	11TB, 8x RAID6, Up to 64TB

I/O Configuration	
SDI Inputs	All SDI ports not used for Playback available as auto-sensing, switchable inputs
IP Inputs	NDI, RTMP Push & Pull, HLS, DASH, RTSP, SRT, TS (UDP/RTP), Zoom, Social Media. Optional Capture
HD/SD Simulcast	Optional, requires 2 ports per Channel
Optional IP Output	ABR Streaming, Transport Stream
Video Routing Switch	Optional Video Routing Switch Control

Storage	
OS/System	SSD
Archive	Optional Archive to NAS (FTP, CIFS) and Archive.org

Content	
File Formats	Import Virtually Any File Format
Video Codecs	MPEG-2, H.264 SD & HD
Audio Codecs	MPEG-1 Layer II, AC-3, AAC, MP3, LPCM
Upload Protocols	Browser Resumable, FTP, CIFS/SAMBA

Recording	
Encode	MPEG-2 Transport (MPEG-2 and H.264 SD/HD)
IP Capture	Optional up to 4 Simultaneous

Playback	
Video Resolutions	SD 480i29.97 NTSC & 576i25 PAL, 720p50/59.94/60, 1080p23.98/24/25/29.97/30, 1080PsF23.98/24/25/29.97/30, 1080i25, 1080i29.97, 1080i30, Automatic up/down-conversion
Audio Format & Channels	48 kHz, 16 bit, Stereo, 8 or 16 Channel
Audio Processing	Optional Real-time Audio Loudness Management (CALM Compliant)
VANCs	CEA-608/708 Closed Captioning, Passthrough

Downstream Graphics	
	Logos, Tickers (Text, RSS/XML, Emergency), Snipes, Squeezebacks, Clocks, Program Guides

Closed Captions	
File	CEA-608/708, Sidecar (WEBVTT, SRT, SCC, MCC), SmartCaption™ File Captioning Integration
Live	CEA-608/708, Optional SmartCaption™ LIVE Integrated Automatic Live Multi-language Captioning

Operating System & High Availability	
	Linux, Watchdog Timer, Solid State System Drive

Network Management	
System Health Notices	SNMP, Email, REST API, and Web Browser UI
Other	Built-in Firewall & Routing Table, Remote Management, Station Timing Locked to NTP

Physical	
Power	100 - 240 VAC / 740 Watts
Dimensions & Weight	17.2" x 3.5" x 25.5" (W x H x D), 35 lbs.
Form Factor	2 RU Rackmount, 19" Standard

External Interfaces & Connections (Typically Used)	
External Reference	Blackburst in SD, 720p50, 720p59.94, 1080i50 and 1080i59.94 formats or Tri-Sync HD in any format
Copper NICs	Quad 10/100/1000BT, Optional Dual Fiber
Front Panel	Power/Fail/Drive LEDs, Power/Reset Switch/ LCD

Application Software	
User Interface	Integrated, Secure Browser-based
Content Management	Custom Metadata and Categories, Video Previews, Integrated Editing, Advanced Search, Bulk Actions, Resumable Browser Uploads, Automatic Publishing, Archiving & Sharing, Optional Archiving & Archive.org Integration, and Bulletin Board.
Scheduling	Automatic Series Scheduling, Drag & Drop, Copy/Paste, Block Copy, Bulk Modify, Recur, Ripple, Import/Export, Auto fill Program Gaps, Auto Start on Trigger / Stop on Signal Loss, Extend Live Events w/ Join-in-Progress, Pause/Resume Recording, Multi-Destination Streaming Rules, Blackout Rules
Graphics	Automatic Overlay Rules, Built-in WYSIWYG Editor, Multiple Simultaneous Overlays, Alpha Channel, Drop Shadow Text, Metadata Variables
Reports	As Run, First/Repeat Run, Missing Files
TV Listing	Embeddable, Searchable Website Program Guide, TV Guide X-List, XMLTV, Minerva, RSS/XML
Traffic & Billing	Optional GDP/CCMS Workflow
APIs	REST, RSS, SNMP
User Management	Scheduling & Emergency Roles, Preferences

Optional Cloud Services	
	Streaming, Mobile & OTT Apps with TelVue CloudCast™, Cloud Contributor Workflow, Media Exchange, SmartCaption™ Automatic Captioning with TelVue Connect™

Note: Specifications are subject to change without notice.



Provided by: Mega Hertz | 800-883-8839 | info@go2mhz.com | www.go2mhz.com

<https://www.go2mhz.com/product/all-in-one-configurable-peg-broadcasting-2/>